



Kronenburg Bv Mac 11 6 X 6

Basic Spec:

- Max Height 3.60 m
- Max Width 2.95 m
- Max Length 11.44 m
- Max vehicle weight 32,6 ton
- Max axle weight 11,2 ton
- Acceleration to 50mph in less than 25sec
- Maximum speed 70mph

Road Engine:

- Detroit Diesel (General Motors)
- Type 8V92TA
- V8 Twin turbocharged and chargecooling
- 710bhp @ 2800 rpm
- Displacement 12.07 ltrs
- Liquid cooled

Pump Engine:

- Detroit Diesel (General Motors)
- Type 6V-53T
- V6
- 300 bhp @ 2300 rpm
- Displacement 5.2 ltrs

Fire Pump:

- Kronenburg type 'I'
- Capacity 6000 ltr/min @12 bar
- Drive – pump engine

Roof Monitor:

- Make – Kronenburg
- Type – manual
- Barrel – air aspirated
- Capacity – 4500 ltr/min
- Range straight stream – 80mtr's
- Range flat fan 30 x 15mtr's
- Min Elevation 70 degree's
- Depression 15 degree's
- Rotation 270 degree's



Foam System:

- Make Kronenburg
- Type Kromatic
- Model – around the pump
- Setting 3% or 6%
- Proportioning system – Electro pneumatic
- Selection – PLC module

Side Deliveries:

- Regulated delivery 1x left & 1x right
- Regulated pressure 7 bar
- Pressure relief valve 8 bar
- Unregulated delivery (yellow) 1x left & 1x right
- Couplings 2 ½ inch instantaneous

Priming System:

- Make - Kronenburg
- Type – water ring

Cab:

- Rear view camera monitor
- Siren system and blue lights
- Central driving position
- Seats 3 people
- Heated mirrors
- Windscreen washers
- Electric windows
- Digital checking system
- Continuous display rev counter
- Continuous display odometer
- Adjustable steering column
- Doors, internal and external operation, with manual override
- Cab heater
- Vac drive off connector
- Tinted glass
- Secondary engine controls

Automatic Transmission:

- Make – Allison (General Motors)
- Type – CLT755 – ATEC
- Speeds Forward – 5



- Speeds Reverse – 1
- Torque convertor
- Stall ratio (approx.) – 1.70

Water tank:

- 11000 ltr's

Foam Tank:

- 1550 ltr's